

Tap offs 4-way DM 36 A/B (F-type connector)

DM 36 A 4012



DM 36 A 4016



DM 36 A 4020



Type	DM 36 A 4012 Tap off, 4-way	DM 36 A 4016 Tap off, 4-way	DM 36 A 4020 Tap off, 4-way
Thru loss 5-1000 MHz	3.5 dB	2.0 dB	1.0 dB
Tap loss 5-1000 MHz	12 dB	16 dB	20 dB
Directional attenuation 5-470 MHz	30 dB	35 dB	35 dB
Directional attenuation 470-1000 MHz	28 dB	30 dB	30 dB
Isolation 5-470 MHz	28 dB	30 dB	30 dB
Isolation 470-1000 MHz	25 dB	28 dB	28 dB
Screening factor	> 85 dB, Class A	> 85 dB, Class A	> 85 dB, Class A
DC-Bypass IN-OUT	no	no	no
Dimensions	78x58x28 mm	78x58x28 mm	78x58x28 mm
Packing unit	5 pieces, bag	5 pieces, bag	5 pieces, bag
Shipping package	25 pieces, 8.1 dm ³ , 2.3 kg	25 pieces, 8.1 dm ³ , 2.3 kg	25 pieces, 8.1 dm ³ , 2.3 kg

Notes

